



3.0 LITRE & ALL TURBO ENGINED VEHICLES
Schedule of Inspection and Maintenance Services

Key to Symbols: A: Adjust R: Replace I: Inspect , correct or replace if necessary									
ITEM	Maintenance Interval (No of months or miles – whichever occurs first)								SEE NOTE
	MONTHS	0	12	24	36	48	60	72	
	X 1000 mls	1	10	20	30	40	50	60	
1. Drive Belts		I	I	I	I	I	I	I	
2. Camshaft Drive Belt							R*		*Excluding 3.0L
3. Engine Oil	R	R	R	R	R	R	R	R	1
4. Engine Oil Filter	R	R	R	R	R	R	R	R	1
5. Engine Coolant	I	I	I	I	I	I	I	R	
6. Cooling System – Hoses/Connections	I	I	I	I	I	I	I	I	
7. Fuel Filter					R*			R	*Excluding 3.0L
8. Air Filter			I	I	R	I	I	R	2
9. Spark Plugs								R	
10. 4 Gas Analysis/Select Monitor Check			I	I	I	I	I	I	
11. Clutch Operation	I	I	I	I	I	I	I	I	
12. Valve Clearance – Adjust at Additional Cost								I	
13. Transmission (Filter Automatic) & Differential Oils	I	I	I	I	R	I	I	R	4
14. Brake and Clutch Fluid	I	I	R	I	R	I	R	R	5
15. Lubrication of Bonnet and Door Catches	I	I	I	I	I	I	I	I	
16. Fuel System Lines and Connections			I	I	I	I	I	I	3
17. Disc Brake Pads and Discs			I	I	I	I	I	I	3
18. Brake Linings and Rear Disc Drums			I	I	I	I	I	I	3
19. Brake Lines			I	I	I	I	I	I	
20. Park and Service Brake Operation			I	I	I	I	I	I	3



21. Front and Rear Axle Shafts and Joints								3
22. Steering and Suspension Systems								3
23. Operation of Lights, Wipers and Washers								
24. Tyre Condition and Inflation Pressures								
25. Full Geometry Check – Front and Rear	PERFORM AS REQUIRED AT AN ADDITIONAL COST							
26. Air Conditioning Service	PERFORM AS REQUIRED AT AN ADDITIONAL COST							
27. Recall Campaign Work or Modifications								

NOTES
1. When the vehicle is used under severe driving conditions mentioned below* - the engine oil & filter should be changed more frequently.
2. When the vehicle is used under severe driving conditions mentioned below* - the air filter element should be changed more frequently.
3. When the vehicle is used under severe driving conditions mentioned below* - inspection should be performed every 6000 miles or 6 months.
4. Auto transmission has front differential. Replace oil when scheduled. When an automatic transmission vehicle is frequently operated under severe conditions, such as pulling a trailer or driving on sand, replacement of automatic transmission fluid and differential gear oils should be performed more frequently.
5. When the vehicle is used under the following conditions the fluid should be changed every 12,000 miles (N/A MODELS S) /10,000 miles (TURBO & 3.0L MODELS) or 12 months whichever occurs first.
* SEVERE DRIVING CONDITIONS
1. Operating in extremely cold weather
2. Pulling a Trailer
3. Repeated Short Trips
4. Driving on Dusty Roads
5. Driving on rough and/or muddy roads
6. Driving in areas using road salt or other corrosive materials
7. Driving for extended periods in coastal areas.